

## QUICK REFERENCE GUIDE - AUTOMATIC SLACK ADJUSTERS

PART NUMBER	SPLINE DIA. / NO. TEETH	LEVER LENGTH	CLEVIS TYPE	CLEVIS THREAD	APPLICATION GUIDE
R 801071	1-1/2" – 28	6"	Straight	5/8" – 18	Steer
R 801073	1-1/2" – 28	5-1/2"	Straight	5/8" – 18	Drive
R 801074	1-1/2" – 28	6"	Straight	5/8" – 18	Trailer
R 801075	1-1/2" – 28	6"	Straight	5/8" – 18	Drive
R 801077	1-1/2" – 28	5"	Straight	5/8" – 18	Steer / Trailer
R 801079	1-1/2" – 28	5-1/2"	Straight	5/8" – 18	Steer

## QUICK REFERENCE GUIDE - MANUAL SLACK ADJUSTERS

PART NUMBER	SPLINE DIA. / NO. TEETH	LEVER LENGTH	CLEVIS TYPE	CLEVIS THREAD	APPLICATION GUIDE
R824000	1-1/2" – 10	5" - 6" - 7"	Straight	1/2"	Eaton/Meritor/Spicer brakes
R824001	1-1/2" — 10	5 1/2" - 6 1/2"	Straight	1/2"	Eaton/Meritor/Spicer brakes
R824007	1-5/8" – 37	6"	Straight	1/2"	Eaton/Fruehauf brakes
R824003	1-1/2" – 28	5" - 6" - 7"	Straight	1/2"	Eaton/Meritor/Spicer brakes
R824004	1-1/2" – 28	5 1/2" - 6 1/2"	Straight	1/2"	Eaton/Meritor/Spicer brakes

## **FEATURES & BENEFITS**

- Keep brakes in constant adjustment
- Eliminate the need for frequent under the truck brake adjustments
- Reduce brake maintenance costs
- Allow optimum brake performance
- 5, 5.5, 6, 6.5 & 7 (inch) slack lengths
- Available for front steer, rear drive and trailer axle applications handed/unhanded

Please refer to PB-8857 for application and part numbers.



Phone:

Fax:

Email: